



Quick-Fix Clamp for Cone Flanges

for quick connections of Combiflex PU conical flanges, weld-on conical flanges and conical flanges with spigots, following DIN 3016

Product Details

Construction / Material

- Specification of the connection solution: Quick-action clamp for conical flanges based on DIN 3016
- Clamp Design: Clamp with turnbuckle, Clamping screw in sizes M5-M10 designed as slotted hexagon screw, accidental opening is prevented by a safety pin
- Material of the clamp: Stainless steel 1.4301

Properties

- Chemical Properties: stainless
- Other: accidental opening is prevented by a safety pin, easy to assemble

Operating Temperature

Delivery Information

Application Areas

Customizing Options

Article Variants

Article number	DN of the hose mm	Piece weight kg	Minimum free space (D) mm	Free space to open (R) mm
002183	50	0.2	147	103
002184	65	0.26	158	103

Article number	DN of the hose mm	Piece weight kg	Minimum free space (D) mm	Free space to open (R) mm
002185	80	0.29	169	103
002186	100	0.46	212	170
002187	125	0.78	241	186
002188	150	0.86	266	202
002189	160	0.91	275	207
002190	180	0.97	289	215
002191	200	1.05	313	228
002192	250	1.24	360	254

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Individual consultation

We offer consultation by
phone:
+49 209 97077-112

Product requests via
[masterflex.de/en](https://www.masterflex.de/en)

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

