



# Master-Tube PA Brake

Special polyamide hose for brake and automotive applications



spiral-free

## Product Details

### Construction / Material

- Execution of the wall: made of highly abrasion-resistant material, made of a material that is insensitive to stress corrosion cracking, made of a material with high impact strength, Dimensions and tolerances correspond to DIN 73378 and manufactured according to DIN 74324

### Properties

- Specifications of the product: manufactured with calibrated outer diameter
- Chemical Properties: good resistance to chemicals, good resistance to oil, good UV resistance, halogen-free, hydrolysis resistant, free from paint wetting impairment substances (LABS)
- Mechanical Properties: small bending radius
- Colour: black

### Operating Temperature

- Temperature Range: -40 - 90

### Delivery Information

- Delivery, type of production: Inner diameter: 2.0 - 16.0 mm, Outer diameter: 4.0 - 20.0 mm

### Application Areas

- Areas of application: Automotive, Plant & Mechanical Engineering, Industry, Sea & rail transport, Cable manufacturers, Vehicle construction

### Customizing Options

- optional item modification (on request): printable, Rolls

### Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

#### Individual consultation

We offer consultation by  
phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://www.masterflex.de/en)

#### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

