



Master-Tube PA-E

Polyamide hose with elastomer components



spiral-free

Product Details

Construction / Material

- Execution of the wall: made of highly abrasion-resistant material, made of a material that is insensitive to stress corrosion cracking, made of a material with high impact strength

Properties

- Specifications of the product: manufactured with calibrated outer diameter
- Chemical Properties: good resistance to solvents, good resistance to oil, good UV resistance, halogen-free, hydrolysis resistant, plasticiser-free, free from paint wetting impairment substances (LABS)
- Physical Properties: flexible at low temperatures

Operating Temperature

- Temperature Range: -40 - 85

Delivery Information

- Delivery, type of production: Inner diameter: 2.0 - 9.0 mm, Outer diameter: 4.0 - 12.0 mm

Application Areas

- Areas of application: Agriculture, Automotive, Plant & Mechanical Engineering, Robotics & Automation, Industry, Semiconductor Industry, Aerospace technology, Bulk & Construction, Sea & rail transport, Chemistry, Surface Technology, Food & Pharma, Waste disposal & cleaning technology, Plastics, Conveying, lifting & feeding technology, Textile, Printing & Paper, Vehicle construction, Metal & Toolmaking

Customizing Options

- optional item modification (on request): other colours, printable, Multiple hose, Spiral version, Shaped hose, Rolls, cut-to-size sections

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Individual consultation

We offer consultation by
phone:
+49 209 97077-112

Product requests via
[masterflex.de/en](https://www.masterflex.de/en)

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

