



## PA Duopart®

Double polyamide hose as burr-free connection solution



spiral-free

### Product Details

#### Construction / Material

- Execution of the wall: made of highly abrasion-resistant material, made of a material that is insensitive to stress corrosion cracking, made of a material with high impact strength, Dimensions and tolerances correspond to DIN 73378 and manufactured according to DIN 74324

#### Properties

- Specifications of the product: manufactured with calibrated outer diameter
- Chemical Properties: good resistance to chemicals, good resistance to solvents, good resistance to oil, good UV resistance, halogen-free, hydrolysis resistant, good resistance to fats, free from paint wetting impairment substances (LABS)
- Mechanical Properties: small bending radius

#### Operating Temperature

- Temperature Range: -40 - 90

#### Delivery Information

- Delivery, type of production: Inner diameter: 2.0 - 8.0 mm, Outer diameter: 4.0 - 10.0 mm

#### Application Areas

- Areas of application: Agriculture, Automotive, Plant & Mechanical Engineering, Robotics & Automation, Industry, Semiconductor Industry, Aerospace technology, Bulk & Construction, Sea & rail transport,

Chemistry, Surface Technology, Food & Pharma, Waste disposal & cleaning technology, Plastics, Conveying, lifting & feeding technology, Textile, Printing & Paper, Vehicle construction, Metal & Toolmaking

### Customizing Options

- optional item modification (on request): other colours, printable, Multiple hose, Rolls

### Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

#### Individual consultation

We offer consultation by  
phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://www.masterflex.de/en)

#### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

