



## XFlame soft®

Flexible PU hose, 85 Shore hardness, self-extinguishing, flame retardant



flame  
retardant



spiral-free

### Product Details

#### Construction / Material

- Execution of the wall: made of highly abrasion-resistant material, made of a material that is insensitive to stress corrosion cracking, made of a material with high impact strength, made of a material with dielectric properties, made of a material with elastic properties
- Specifications of the wall: Flame resistance tested according to UL 94 V2 - V0

#### Properties

- Chemical Properties: good resistance to oil, good UV resistance, halogen-free, hydrolysis resistant, microbe-resistant, plasticiser-free, good resistance to fats, free from paint wetting impairment substances (LABS)
- Mechanical Properties: small bending radius, Kink-resistant
- Physical Properties: flexible at low temperatures, good damping behaviour

#### Operating Temperature

- Temperature Range: -40 - 90

#### Delivery Information

- Delivery, type of production: Inner diameter: 2.0 - 11.0 mm, Outer diameter: 4.0 - 16.0 mm

#### Application Areas

- Areas of application: Agriculture, Automotive, Plant & Mechanical Engineering, Robotics & Automation, Industry, Aerospace technology, Sea & rail transport, Surface Technology, Food & Pharma, Plastics,

Conveying, lifting & feeding technology, Textile, Printing & Paper, Vehicle construction, Metal & Toolmaking

### Customizing Options

- optional item modification (on request): other colours, printable, Multiple hose, Spiral version, Shaped hose, Rolls, cut-to-size sections

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

### Individual consultation

We offer consultation by  
phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://www.masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

