



## Cuff for Master-PVC-Flex

special coupling for connecting Master-PVC Flex hoses

### Product Details

#### Construction / Material

- material of the cuff: soft PVC

#### Properties

- Chemical Properties: good resistance to chemicals, stainless, odourless and tasteless
- Mechanical Properties: kink-proof
- Other: easy to assemble

#### Operating Temperature

- Temperature Range: 0 - 70

#### Delivery Information

- Delivery, type of production: Various nominal widths are available ex production, individual nominal widths also ex stock, individual nominal widths also ex stock

#### Application Areas

#### Customizing Options

### Article Variants

Article number	DN of the hose mm	Outer diameter of the pipe (AD) mm	Outer diameter on the hose side (AD) mm	Clamping range outside mm	Screw-in depth of the hose mm	Piece weight kg	Length mm
002536	25	25	38,0	32	44	not specified	98

Article number	DN of the hose mm	Outer diameter of the pipe (AD) mm	Outer diameter on the hose side (AD) mm	Clamping range outside mm	Screw-in depth of the hose mm	Pieceweight kg	Length mm
002537	32	32	43,0	40	44	not specified	98
002538	38	38	49,0	47	48	not specified	98
002540	44	44	59,0	53	48	not specified	98
002541	51	51	63,0	59	48	not specified	98
002543	63	63	73,0	70	48	not specified	98
002544	70	70	86,0	78	54	not specified	98
002545	76	76	93,0	84	54	not specified	98
002547	102	100	118,0	108	65	not specified	113

Subject to technical changes and colour deviations

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

### Individual consultation

We offer consultation by phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://www.masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

