



## Cuff for Master-VAC

Special sleeve for connection of Master-VAC hoses, electrically conductive

### Product Details

#### Construction / Material

- design of the cuff: made of electrically conductive material
- material of the cuff: Polyethylene
- material specification of the cuff: Surface resistance  $R_0 < 10^6$  Ohm

#### Properties

- Chemical Properties: odourless and tasteless, good resistance to chemicals, stainless
- Other: easy to assemble

#### Operating Temperature

- Temperature Range: 0 - 70

#### Delivery Information

- Delivery, type of production: Available from stock in the stated nominal widths in black

#### Application Areas

#### Customizing Options

- optional item modification (on request): other nominal widths

### Article Variants

Article number	DN of the hose mm	Outer diameter of the pipe (AD) mm	Outer diameter on the hose side (AD) mm	Clamping range outside mm	Screw-in depth of the hose mm	Insertion depth of the threaded socket mm	Piece weight kg	Length mm
002531	32	32	44.5	37.5 - 38.5	38	55.5	0.035	93.5

Article number	DN of the hose mm	Outer diameter of the pipe (AD) mm	Outer diameter on the hose side (AD) mm	Clamping range outside mm	Screw-in depth of the hose mm	Insertion depth of the threaded socket mm	Piece weight kg	Length mm
002532	38	38	52	44.5 - 45.75	38	55.5	0.046	93.5
002533	45	45	58.5	50 - 51	38	55.5	0.049	93.5
002534	50	50	66	57 - 58.5	38	55.5	0.059	93.5

Subject to technical changes and colour deviations

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

### Individual consultation

We offer consultation by phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://www.masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

